



GSX-R600W



GSX-R600W

GSX-R600W

1992

KEY FEATURES

Engine

- Compact 4-cylinder, 4-stroke DOHC engine
- High efficiency liquid-cooling system
- Oil-jet piston cooling system
- Liquid-cooled oil cooling system
- Lightweight shim-under-bucket valve train
- 36mm Mikuni slingshot carburetors
- Digital ignition system with maintenance-free battery
- Close ratio 6-speed transmission
- Stainless steel 4 into 2 into 1 exhaust system

Frame/Suspension

- Rigid double-cradle aluminum frame
- Bolt-on seat support section
- Curved, G.P.-style aluminum swingarm
- Showa cartridge-type inverted front forks
- Link-type rear suspension with remote reservoir shock absorber
- 310mm front disk brakes with floating rotors & 4-piston calipers
- Adjustable front brake lever
- 240mm rear disc brake with 2-piston caliper
- 3-spoke cast aluminum wheels with radial tires
- New-style fairing with fresh air intake ducts
- Flush mounted halogen headlamps
- 5.5 gallon fuel tank with additional frame sidecovers

**Courtesy of
eBay Seller:**

KAWASAKI-YAMA-ZUKI

PLEASE NOTE:

This product is in development and scheduled for March 1992 availability. These specifications are not final and are subject to change.

SPECIFICATIONS

Engine:

600cc, 4 stroke, 4 cylinder, water-cooled, DOHC, 16 valve, TSCC

Bore/Stroke:

65.0 x 45.2mm

Compression Ratio:

12.0:1

Carburetor:

Four Mikuni BST36SS

Lubrication:

Wet sump

Ignition:

Fully transistorized

Starter:

Electric

Transmission:

6 speed, constant mesh

Final Drive:

RK50GSVZ1 chain

Overall Length:

2085mm (82.1 in.)

Overall Width:

725mm (28.5 in.)

Overall Height:

1140 mm (44.8 in.)

Seat Height:

780 mm (30.7 in.)

Wheelbase:

1435mm (56.5 in.)

Ground Clearance:

130mm (5.1 in.)

Dry Weight:

208kg (459 lbs.) 212kg (467 lbs.) CA model

Suspension:

FRONT

Inverted telescopic, coil spring, spring preload fully adjustable, damping force compression 12-way and rebound compression 12-way and extension 12-way adjustable

REAR

Link type, coil spring, gas/oil damped, spring preload fully adjustable, damping force compression 12-way and rebound 4-way adjustable.

Brakes:

FRONT

Dual hydraulic disc

Tires:

REAR

Single hydraulic disc

FRONT

120/70-ZR-17

REAR

170/160-ZR-17

Fuel Tank Capacity:

21.0 liter (5.5 gal.)

18.5 liter (4.8 gal.) CA model

Colors:

White/Red, Black/Blue



The ride you've been waiting for™